



Eaton Basic ePDUs

Single-phase power distribution solutions up to 30 amps.

The Eaton® Basic ePDU® product line is designed to provide high reliability power distribution to critical power loads. These units feature a small form factor and lightweight chassis that is easy to mount. Rackmount models feature a rotating mounting bracket that allows for vertical mounting. Vertical models offer blind mount bracket and keyhole button mounting options. The high outlet density and a variety of plug/receptacle configurations make it easy to find a configuration that meets your needs. These configurations are stocked for high availability.

Key features and benefits:

- Cord lengths up to 15 feet
- Rackmount or 24", 48" and 60" lengths for outlet accessibility
- High outlet density up to 36 outlets
- Variable clip foot and button mounting options
- Single-phase 15A to 30A, 120-volt and 240-volt configurations
- UL 60950 approved for IT or data center use

EATON
Powering Business Worldwide



1U RACKMOUNT EPDUS

Catalog Number	Input Plug	Breaker	Max kW	Cord (ft)	Receptacles	Dimensions (H x W x D, in)
EFLXL1500R-PDU1U	5-15P	None	1.44	3	(12) 5-15R	1.7 x 19.0 x 2.4
ePBZ86	5-15P	None	1.44	10	(12) 5-15R	1.7 x 17.3 x 2.3
ePBZ83	5-15P	None	1.44	15	(12) 5-15R	1.7 x 17.3 x 2.3
EFLXL2000R-PDU1U	5-20P	None	1.92	3	(12) 5-20R	1.7 x 19.0 x 2.4
EFLXL2000R-PDU1UL	5-20P	None	1.92	3	(5) L5-20R	1.7 x 19.0 x 3.0
ePBZ85	5-20P	None	1.92	10	(12) 5-20R	1.7 x 17.3 x 2.3
ePBZ99	L5-20P	(1) 20A	1.92	6	(12) 5-20R	1.7 x 19.0 x 2.4
ePBZ82	L5-20P/5-20P*	None	1.92	15	(12) 5-20R	1.7 x 17.3 x 2.3
ePBZ84	L5-30P	(2) 20A	2.88	10	(10) 5-20R	1.7 x 17.0 x 3.5
ePBZ78	L5-30P	(2) 20A	2.88	15	(20) 5-20R	1.7 x 17.0 x 3.5
EFLXI3000R-PDU1UIEC	C20 Inlet	(2) 20A	3.33	3	(12) C13, (1) C19	1.7 x 19.0 x 2.4
ePBZ88	C20	None	3.33	6	(10) C13, (2) C19	1.7 x 19.0 x 2.4
ePBZ95	L6-20P	None	3.33	6	(12) C13, (1) C19	1.7 x 19.0 x 2.4
ePBZ94	L6-30P	(2) 20A	4.99	6	(6) C19	1.7 x 19.0 x 2.4
ePBZ91	L6-30P	(2) 20A	4.99	10	(10) C13	1.7 x 17.0 x 3.5
ePBZ79	L6-30P	(2) 20A	4.99	15	(16) C13, (4) C19	1.7 x 17.0 x 5.1

0U VERTICAL MOUNT EPDUS

Catalog Number	Input Plug	Breaker	Max kW	Cord (ft)	Receptacles	Dimensions (H x W x D, in)
ePBZ75	5-15P	None	1.44	15	(14) 5-15R	23.9 x 1.5 x 1.5
ePBZ98	5-15P	(1) 15A	1.44	6	(18) 5-15R	40.0 x 1.5 x 1.5
ePBZ73	5-15P	(1) 15A	1.44	15	(18) 5-15R	48.0 x 1.5 x 1.5
ePBZ97	5-20P	(1) 20A	1.92	6	(24) 5-20R	48.0 x 1.5 x 1.5
ePBZ96	L5-20P	(1) 20A	1.92	6	(24) 5-20R	48.0 x 1.5 x 1.5
ePBZ74	L5-20P/5-20P*	None	1.92	15	(14) 5-20R	23.9 x 1.5 x 1.5
ePBZ72	L5-20P/5-20P*	(1) 20A	1.92	15	(18) 5-20R	48.0 x 1.5 x 1.5
ePBZ77	L5-20P/5-20P*	(1) 20A	1.92	15	(24) 5-20R	60.0 x 1.5 x 1.5
ePBZ71	L5-20P/5-20P*	(1) 20A	1.92	15	(30) 5-20R	72.0 x 1.5 x 1.5
ePBZ90	L5-30P	(2) 20A	2.88	15	(24) 5-20R	40.0 x 1.9 x 2.1
ePBZ89	C14	None	2.88	6	(16) C13	28.0 x 1.9 x 2.2
ePBZ93	L6-20P	None	3.33	10	(20) C13, (4) C19	40.0 x 1.9 x 2.2
ePBZ92	L6-30P	(2) 20A	4.99	10	(20) C13, (4) C19	42.0 x 1.9 x 2.2
ePBZ80	L6-30P	(2) 20A	4.99	10	(30) C13, (6) C19	52.9 x 1.9 x 2.2

*These units ship with an adapter allowing for 5-20P input plug

